



VHF MARINE TRANSCEIVER

IC-M88 UL Version

Marine Radio for Hazardous Locations

5 W Output Power for Hazardous Locations

The IC-M88 UL version provides 5 W output power and can be used in hazardous locations, stipulated under Class I, Division 2 conditions of use approved by UL.

Nonincendive: Class I, Division 2, Groups A, B, C, D T6 ($\leq 85^{\circ}\text{C}$) when used with Icom BP-227UL battery pack.

Approved accessories: Speaker-microphone, HM-168IS

Ambient temperature: -20°C to $+40^{\circ}\text{C}$

ANSI/ISA 12.12.01

IPX7, Waterproof Construction

The IC-M88 UL version is built tough to withstand hazardous and inhospitable environments at sea and on land. Even if the IC-M88 UL version is dropped into water, the IPX7 waterproof construction will protect it from harm (1 m depth for 30 minutes). The compact and durable body also has been tested to U.S. military specifications (MIL-STD 810).

Rechargeable Li-ion Battery for Extra Long Battery Life

With the standard 1950 mAh (typ.) Li-Ion battery pack, BP-227UL, the IC-M88 UL version allows you up to 19 hours of operating time.*

* Typical operation; Tx:Rx:Stand-by duty ratio = 5:5:90

22 Programmable Channels for LMR Use

The IC-M88 UL version has 22 programmable channels for LMR use* (146–174 MHz). CTCSS and DTCS signaling is built-in.

*Appropriate license will be required.

Optional Waterproof Speaker-Microphone, HM-168IS

An optional waterproof speaker-microphone, HM-168IS, provides reliable operation, allowing you to wear the IC-M88 on your belt for added portable convenience.

Built-in Voice Scrambler

The IC-M88 UL version has a built-in 32 code voice scrambler, depending on version. The voice scramble is compatible with the UT-112 which is adopted to some Icom marine radios.



Photo includes optional speaker-microphone, HM-168IS.

Additional features

- Selectable 5/3/1 W output power
- Auto WX scan and WX alert function
- Simple Up/Down switches for operating channel selection
- Instant access to Ch. 16 and Ch. 9 (or call channel)
- Simple add/delete TAG scanning operation
- Battery indicator shows remaining battery power in 4 levels
- Beep sound is programmable for each button
- The self check function checks internal temperature, connected battery voltage (over voltage detection), and water intrusion
- Monitor button opens squelch
- Key lock function
- Automatic scan function
- 2 step power saver

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.

BATTERY PACK



BP-227UL
Rechargeable Li-Ion
1850 mAh (min.),
1950 mAh (typ.)

DESKTOP CHARGER



BC-147SA **BC-152N**
Charges the BP-227UL in 9-10 hours.
(approx.)

RAPID CHARGER



BC-123SA **BC-190**
Rapidly charges the BP-227UL in 2.5-3
hours. (approx.)

MULTI-CHARGER



BC-197 **BC-157S**
Rapidly charges up to 6 battery packs in 2.5-3 hours.
AD-128 is supplied with the BC-197, depending on version.

CIGARETTE LIGHTER CABLE



CP-23L
For use with BC-152N

DC POWER CABLES



OPC-515L **OPC-656**
For use with BC-152N For use with BC-197

SPEAKER-MICROPHONE



HM-1681S

LEATHER BELT HANGERS



MB-96N **MB-96F** **MB-96FL**
Swivel type Fixed type Long type

BELT CLIPS



MB-98 **MB-86**
Alligator type Swivel type

DO NOT use the transceiver with any other equipment other than the above options. The following battery chargers, BC-152N, BC-190 or BC-197 MUST NOT be used in an explosive atmosphere.

Please ensure the IC-M88 UL version ratings are acceptable for the intended place of use, at Icom website "http://www.icom.co.jp/products/marine/handheld/IC-M88_UL/". Please note there are classification differences between the IC-M88 UL and IC-M88 FM version.

Read all instructions enclosed with the transceiver carefully and completely before using the transceiver.

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. All other trademarks are the properties of their respective holders.

SPECIFICATIONS

IC-M88 UL Version		
GENERAL	Marine channels	LMR channels
Frequency coverage Tx Rx	156.025-157.425 MHz 156.050-163.275 MHz	146.000-174.000 MHz
Usable channel groups, Number of channels	INT, USA, CAN, WX channels	22 LMR channels
Type of emission	16K0G3E	8K50F3E
Channel spacing	25 kHz	12.5 kHz
Power supply requirement	7.4 V DC nominal	
Current drain (approx.) Tx (at 5 W) Rx Max. audio	1.6 A typ. 200 mA typ.	
Antenna impedance	50 Ω (SMA type)	
Operating temperature range	-20°C to +60°C; -4°F to +140°F	-30°C to +60°C -22°F to +140°F
Dimensions (W×H×D) (Projections not included)	62 × 97 × 39 mm; 2.44 × 3.82 × 1.54 in (With BP-227UL)	
Weight (approx.)	280 g; 9.9 oz (With BP-227UL)	
TRANSMITTER		
Output power (Hi/Mid/Low)	5/3/1 W	
Max. frequency deviation	±5.0 kHz	±2.5 kHz
Audio harmonic distortion	Less than 10% (at 60% deviation)	
Spurious emissions	-70 dBc typ.	
Adjacent channel power Hum and noise ratio	70 dB 40 dB	60 dB 34 dB
RECEIVER		
Sensitivity (at 12 dB SINAD)	0.25 μV typ.	
Squelch sensitivity	0.35 μV typical (at threshold)	
Adjacent channel selectivity	70 dB typ.	60 dB typ.
Intermodulation rejection	70 dB typ.	
Spurious response	70 dB typ.	
Hum and noise	40 dB	34 dB
Audio output power	350 mW (at 10% distortion with 8 Ω load)	

Measurements made in accordance with TIA/EIA-603.

All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810 G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	-
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standard

Water IPX7 (Waterproof protection)

Supplied accessories: (*Varies according to version.)

- Battery pack
- Battery charger
- AC adapter*
- Swivel belt clip
- Antenna, FA-S59V
- Hand strap

Icom Inc.

1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.

12421 Willows Road NE,
Kirkland, WA 98034, U.S.A.
Phone: +1 (425) 454-8155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>

Icom (Europe) GmbH

Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone: +49 (6196) 76685-0
Fax: +49 (6196) 76685-50
E-mail: info@icom-europe.com
URL: <http://www.icomeurope.com>

Icom France s.a.s.

Zac de la Plaine,
1 Rue Brindejonc des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone: +33 (5) 61 36 03 03
Fax: +33 (5) 61 36 03 00
E-mail: icom@icom-france.com
URL: <http://www.icom-france.com>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada

Glenwood Centre #150-6165
Highway 17A, Delta, B.C.,
V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: icom@icomspain.com
URL: <http://www.icomspain.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone: +61 (03) 9549 7500
Fax: +61 (03) 9549 7505
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Icom Brazil

Rua Iitoró, 444 Padre Eustáquio
Belo Horizonte MG,
CEP: 30720-450, Brazil
Phone: +55 (31) 3582 8847
Fax: +55 (31) 3582 8987
E-mail: sales@icombrasil.com

Icom (UK) Ltd.

Blacksloe House, Altira Park,
Herne Bay, Kent, CT6 6GZ, U.K.
Phone: +44 (0) 1227 741741
Fax: +44 (0) 1227 741742
E-mail: info@icomuk.co.uk
URL: <http://www.icomuk.co.uk>

Icom New Zealand

39C Rennie Drive, Airport Oaks,
Auckland, New Zealand
Phone: +64 (09) 274 4062
Fax: +64 (09) 274 4708
E-mail: inquiries@icom.co.nz
URL: <http://www.icom.co.nz>